

578 Countertop Payment Terminal

PAX's S78 is a unique sprocket printer enabled POS terminal, offering all the performance and security of traditional countertop devices, to merchants with special receipt or voucher printing requirements.

With a powerful 32-bit ARM11 processor, the S78 is ideally suited to both EMV and value-added transactions.

The S78 can be readily adapted to a variety of merchant environments, given the many connectivity options, including Ethernet & GPRS, and the many peripheral ports available.



578 Countertop Payment Terminal

FEATURES & BENEFITS







- PCI PTS 4.x certified
- EMV L1 & L2 compliant
- Large memory capacity
- Optional contactless card reader
- USB connectivity
- Supports multiple applications

SPECIFICATIONS

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

2.8 inch 320 x 240 pixels TFT color LCD

Keypad

10 numeric & 9 function keys

Printe

Sprocket printer (76mm width) Speed: 4 lines per second

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader (optional)

13.56MHz, ISO14443 Type A/B Mifare *, Felica, NFC 4 RF Indicators

Card Slots

4 SAM Slots 1 SIM (optional)

Communication

Modem: Sync. (HDLC up to 9600bps) Async. (V.92, up to 56Kbps)

Ethernet

GPRS (optional) WiFi (optional)

Peripheral Ports

2 x RS232, 1 x PINpad, 1 x Ethernet, 1 x Line, 1 x TEL, 1 x mini USB

Security

DUKPT, Master/Session, DES, 3DES ANSI/ISO9564 format 0, 1, 3 PIN ciphered key algorithm ANSI X9.9/X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating temperature 10% to 93% relative humidity, non-condensing -20°C to 70°C (-4°F to 158°F) storage temperature

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.5A Output: 24VDC, 1.8A

Physical

Length: 315mm Width: 153mm Height: 126mm

Weight

1300g

Certifications

PCI PTS 4.x EMV Level1 & Level2



