



S80 Countertop Payment Terminal

- **Contactless, Chip, Magstripe**
- **Large memory capacity**
- **Dial, Ethernet**
- **High Speed Printer**
- **PCI PTS 4.x, SRED**

PAX's S80 is an advanced countertop POS terminal which combines ease-of-use, durability and high performance to assure faster, more reliable transactions.

The PCI PTS 4.x approved S80 offers advanced connectivity, equipped with various communication technologies such as Dial, Ethernet. An intuitive ATM style interface and ergonomic keypad make operation easier for merchant and consumer alike.

The S80 comes with built-in contactless and powerful ARM11 processor, enabling support for multiple payment and value-added applications, making this countertop terminal one of the most reliable in the world.

Your Payment Partner of Choice



S80 Countertop Payment Terminal

Features & Benefits



- High speed ARM 11 processor
- Large memory capacity
- Dial, Ethernet
- Built-in contactless
 - MasterCard Contactless
 - Visa payWave
 - American Express ExpressPay
 - Discover DPAS
 - JCB J/Speedy

Specifications

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

2.4 inch 320 x 240 TFT color LCD

Keypad

10 numeric / letter keys, 8 function keys
4 ATM keys, 1 Power ON / OFF key

Printer

Thermal printer, speed: 30 lines per second
Paper roll width / diameter: 58mm / 50mm

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader (optional)

MasterCard Contactless & Visa payWave
American Express ExpressPay
Discover D-Pass
JCB J/Speedy
ISO / IEC 14443 Type A / B,
Mifare®, Felica, NFC
4 RF Indicators

Communication

Modem: Sync. (HDLC, up to 9600bps)
Async. (V.92, up to 56kbps)

Ethernet

Peripheral Ports

1 x PINPad, 1 x RS232, 1 x Ethernet
1 x Line, 1 x Mini USB (OTG), 1 x Power port

Security

PCI PTS 4.x approved
DUKPT, Master / Session, 3DES
ANSI / ISO9564 format 0, 1, 3
PIN ciphered key algorithm
ANSIX9.9 / X 9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.5A
Output: 9VDC, 1A

Physical

Length: 8.50inches
Width: 3.74inches
Height: 3.39inches

Weight

18.52oz

Certifications

PCI PTS 4.x
EMV L1 & L2
MasterCard Contactless
Visa payWave
American Express ExpressPay
Discover DPAS
JCB J/Speedy

www.pax.us

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2016, PAX Technology Limited, All Rights Reserved.


PAX
Your Payment Partner of Choice