

S90 Mobile Payment Terminal

PAX's S90 mobile POS terminal has been designed to offer superior wireless performance, embedded in a ruggedized yet stylish form factor. With multiple communication options such as single SIM or dual SIM GPRS, CDMA, WiFi and 3G, as well as large memory and high capacity Li-ion rechargeable battery, the S90 is one of the most popular mobile terminals with merchants today.

The S90 comes with inbuilt contactless, PCI PTS 3.x certification and delivers secure transactions using an ARM11 processor to support DUKPT, Master/Session, DES and 3DES.



S90 Mobile Payment Terminal

FEATURES & BENEFITS



- High speed ARM 11 processor
- Large memory capacity
- Optional built-in contactless
 - MasterCard PayPass
 - Visa payWave
- Optional 1D barcode scanner
- USB & 3G connectivity
- Large capacity battery
- GPRS (also dual-SIM), CDMA, 3G

SPECIFICATIONS

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

128 x 64 pixel LCD

Keypad

10 numeric / letter keys, 8 function keys 4 ATM keys, 1 Power ON / OFF key

Printe

Thermal printer, speed: 18 lines per second Paper roll width / diameter: 58mm / 38mm

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless card Reader (optional)

MasterCard PayPass & Visa payWave 13.56MHz, ISO / IEC 14443 Type A / B, Mifare®, Felica, NFC 4 RF Indicators

Card Slots

2 SAMs 1 SIM

Barcode Reader (optional)

1D barcode scanner

Communication

GPRS / CDMA / 3G (WCDMA) Modem (optional): Sync. (HDLC up to 9600bps) Async. (V.92, up to 56Kbps)

Peripheral Ports

1 x RS232, 1x mini USB (OTG) 1 x Line (optional), 1 x power charge

Security

PCI PTS 3.x approved DUKPT, Master / Session, DES, 3DES ANSI / ISO9564 format 0, 1, 3 PIN ciphered key algorithm ANSI X9.9 / X9.19 MAC algorithm

Environmental

 $0^{\circ}C$ to $50^{\circ}C$ ($32^{\circ}F$ to $122^{\circ}F)$ operating temperature $-20^{\circ}C$ to 70° C (- $4^{\circ}F$ to $158^{\circ}F)$ storage temperature 10% to 93% relative humidity, non-condensing

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.0A Output: 9.5VDC, 4A

Battery

Li-ion battery 1800mAh, 7.4V

Physical

Length: 199mm Width: 87mm Height: 61.5mm

Weight

504g with battery

Accessories (optional)

Leather Casing Charging Dock Car Jack Charger

Certifications

PCI PTS 3.x EMV L1 & L2 MasterCard PayPass Visa payWave EMV Contactless L1

